

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 January 2001 (18.01.2001)

PCT

(10) International Publication Number  
**WO 01/03912 A1**

(51) International Patent Classification\*: **B29D 31/00**,  
B29C 43/36, B29D 30/48, B29C 70/46

(21) International Application Number: PCT/US99/15940

(22) International Filing Date: 13 July 1999 (13.07.1999)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **THE  
GOODYEAR TIRE & RUBBER COMPANY** [US/US];  
1144 East Market Street, Akron, OH 44316-0001 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **REX, William,  
Allen** [US/US]; 18220 William Drive, Doylestown, OH  
44230 (US). **CONGER, Kenneth, Dean** [US/US]; 1332  
Homesite Drive, Stow, OH 44303 (US). **WILSON, Brian,  
Joseph** [US/US]; 52 Royal Avenue, Akron, OH 44303  
(US).

(74) Agent: **LACHER, Frederick, K.**; Brown, Robert, W., The  
Goodyear Tire & Rubber Company, Patent Counsel, 1144  
East Market Street, Akron, OH 44316-0001 (US).

(81) Designated States (national): AL, AM, AT, AU, AZ, BA,  
BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES,  
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG,  
MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE,  
SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN,  
YU, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM,  
AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT,  
BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,  
NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,  
GN, GW, ML, MR, NE, SN, TD, TG).


Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **BEAD CURING FINGER MOLD**

(57) Abstract: A tire bundle is molded in a mold cavity formed by closing a mold having upper and lower mold halves with intermeshing fingers (20, 24) for enclosing bead wires and providing a molded bead ring for placing in a bead apex mold.



WO 01/03912 A1